

\$SPAD/src/input pdecomp0.as

The Axiom Team

July 31, 2014

Abstract

Contents

1	License
---	---------

3

1 License

```
-- Copyright (c) 1991-2002, The Numerical Algorithms Group Ltd.
-- All rights reserved.
--
-- Redistribution and use in source and binary forms, with or without
-- modification, are permitted provided that the following conditions are
-- met:
--
--   - Redistributions of source code must retain the above copyright
--     notice, this list of conditions and the following disclaimer.
--
--   - Redistributions in binary form must reproduce the above copyright
--     notice, this list of conditions and the following disclaimer in
--     the documentation and/or other materials provided with the
--     distribution.
--
--   - Neither the name of The Numerical Algorithms Group Ltd. nor the
--     names of its contributors may be used to endorse or promote products
--     derived from this software without specific prior written permission.
--
-- THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
-- IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
-- TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
-- PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
-- OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
-- EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
-- PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
-- PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
-- LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
-- NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
-- SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
```

— * —

```
#pile
#include "axiom.as"

--% Polynomial composition and decomposition functions
-- If  $f = g \circ h$  then  $g = \text{leftFactor}(f, h)$  &  $h = \text{rightFactor}(f, g)$ 
-- SMW Dec 86

--% PolynomialComposition
--)abbrev package PCOMP PolynomialComposition
--)abbrev package PDECOMP PolynomialDecomposition

PolynomialComposition(UP: UnivariatePolynomialCategory(R), R: Ring): with
  compose: (UP, UP) -> UP
```

```

== add
  compose(g:UP, h:UP):UP ==
    r: UP := 0
    while g ~= 0 repeat
      r := leadingCoefficient(g)*h**degree(g) + r
      g := reductum g
    r

-- Ref: Kozen and Landau, Cornell University TR 86-773

--% PolynomialDecomposition

PolynomialDecomposition(UP:UPC F, F:Field): PDcat == PDdef where
  UPC ==> UnivariatePolynomialCategory
  NNI ==> NonNegativeInteger
  LR ==> Record(left: UP, right: UP)

PDcat ==> with
  decompose: UP -> List UP
  decompose: (UP, NNI, NNI) -> Union(value1:LR, failed:'failed')
  leftFactor: (UP, UP) -> Union(value1:UP, failed:'failed')
  rightFactorCandidate: (UP, NNI) -> UP
PDdef ==> add

  import from F
  import from LR
  import from Union(value1:UP, failed:'failed')
  import from Float
  import from NNI
  import from UniversalSegment NNI
  import from Record(quotient:UP, remainder:UP);

  leftFactor(f:UP, h:UP):Union(value1:UP, failed:'failed') ==
    g: UP := 0
    for i in 0.. while f ~= 0 repeat
      fr := divide(f, h)
      f := fr.quotient
      r := fr.remainder
      degree r > 0 => return [failed]
      g := g + r * monomial(1, i)
    [g]

  decompose(f:UP, dg:NNI, dh:NNI):Union(value1:LR, failed:'failed') ==
    df := degree f
    dg*dh ~= df => [failed]
    h := rightFactorCandidate(f, dh)
    g:Union(value1:UP, failed:'failed') := leftFactor(f, h)

```

```

g case failed => [failed]
[[g.value1, h]]

decompose(f:UP):List UP ==
df := degree f
for dh in 2..df-1 | df rem dh = 0 repeat
  h := rightFactorCandidate(f, dh)
  g := leftFactor(f, h)
  g case value1 => return
  append(decompose(g.value1), decompose h)
[f]

rightFactorCandidate(f:UP, dh:NNI):UP ==
f := f / leadingCoefficient f
df := degree f
dg := df quo dh
h := monomial(1, dh)
for k in 1..dh repeat
  hdg:= h**dg
  c := (coefficient(f,df-k)-coefficient(hdg,df-k))/
      (dg::Integer::F)
  h := h + monomial(c, dh-k)
h - monomial(coefficient(h, 0), 0) -- drop constant term

```

References

- [1] nothing